Nan	ne	Tap & Go (4.2")	Tap & Go (4.9″)
Model		G137 (Right hand) G138 (Left hand)	G128
0:	Outer diameter	φ106mm (4. 2")	φ124mm (4. 9")
Size	Height	63. 5mm	66.3mm
Weig	, sht	250g 340g	
Height from the ground to the exit of nylon line		39. 5mm	38. 3mm
Applicable	Diameter	φ2. 0~ φ2. 8mm	φ2. 0~ φ3. 0mm
nylon line	Length	4m (φ2. 4mm base)	8m (<i>ф</i> 2. 4mm base)
Nylon line length con	ning out by one tap	30mm-33mm	32mm-40mm
Rotating o	direction	G137 (Right hand)/G138 (Left hand)	Left
Photo View			

Tap and Go					
Name		Dual Easy Loader (4.2″)			
Model		G162	G166 (universal fitting)		
0'	Outer diameter	φ107mm (4. 2")	φ107mm (4. 2")		
Size	Height	72. 5mm	70mm		
Weight		300g	350g		
Height from the ground to the exit of nylon line		38mm	42mm		
Applicable	Diameter	φ2. 0~ φ2. 8mm	φ2. 0~ φ2. 8mm		
nylon line	Length	4m (φ2. 4mm base)	4m (φ2. 4mm base)		
Nylon line length coming out by one tap		30mm-33mm	30mm-33mm		
Rotating o	direction	Left hand	Left hand		
View					

Tap and Go				
Name		Dual Easy Loader(5.5")		
Model		G182		
Size	Outer diameter	φ140mm (5. 5")		
	Height	74. 5mm		
Weight		550g		
Height from the ground to the exit of nylon line		42mm		
Applicable	Diameter	φ2. 4~φ3. 5mm		
nylon line	Length	6m (φ3mm base)		
Nylon line length com	ing out by one tap	31mm-48mm		
Rotating d	irection	Left hand		
View				

Tap and Go				
Name		Buttonless (4.3")		
Model		G102 (Female) / G104 (Male)		
Size	Outer diameter	φ110mm (4. 3")		
	Height	50mm		
Weight		260g		
Height from the ground to the exit of nylon line		28mm		
Applicable	Diameter	φ2. 0~ φ2. 4mm		
nylon line	Length	6m (φ2. 4mm base)		
Nylon line length com	ning out by one tap	35mm		
Rotating o	lirection	Left hand		
View				